

V 62 ADJUSTABLE WRENCH

- > Chrome Vanadium steel 31CrV3.
- > Swedish pattern. Jaw set at 15°.
- > Blackened finish. Ground head.
- > Moulded PVC handle.
- > Insulated up to 1000V.
- > Protective guard.
- > Due to the adjusting knurl not being insulated,
- > this tool is not certified to VDE.



Code	No.	↳ mm ↲	mm ↲	⚖ kg
636854	V 62 / 200H*	200	25	0.250
636858	V 62 / 250H	250	30	0.460
636862	V 62 / 300H	300	36	0.700

VDE 4507 TORQUE WRENCH 1/2"

⚡ 1000 V

5-50 N·m / 4-37 lbf·ft

- > Controlled screw tightening in the most common range of 5 - 50Nm / 4 - 37 lbf·ft.
- > Automatic short-path actuation with tactile impulse and audible signal.
- > Dual scale with a scale graduation of 5Nm and 5lbf·ft.
- > Fine toothed ratchet with square drive as per DIN 3120 - A 12.5, ISO 1174.
- > VDE insulation up to 1000V, according to EN 60900/IEC 60900, two-ply Check-Tool insulation.



Code	No.	□, □	□	↳ mm ↲	⚖ kg
6681920	VDE 4507-4	1/2	12.5	370	1.251

VDE 2160 PH PHILLIPS SCREWDRIVERS



⚡ 1000 V

for cross-head screws PH

- > Individually tested, VDE insulation up to 1000 V, acc. to EN 60900/IEC 60900, fully insulated blade
- > Blade tip to DIN ISO 8764-1 PH
- > 3-component handles Power-Grip³ with hanging hole
- > Ergonomic handle design enables precise and fatigue-free working
- > Positive-fit joint of handle and blade for optimum transmission of force
- > Type of drive marked at end of the handle
- > Blade from GEDORE molybdenum-vanadium-Plus tempered steel



Code	No.	⊕	⊕	↳ mm ↲	⚖ kg
1612115	VDE 2160 PH1	M2 - M3	1	180	0.082
1612123	VDE 2160 PH2	M3,5 - M5	2	210	0.119
1612131	VDE 2160 PH3	M5,5 - M7	3	270	0.188

VDE 2170 ELECTRICIAN'S SCREWDRIVERS



⚡ 1000 V

for slotted head screws

- > Individually tested, VDE insulation up to 1000 V, acc. to EN 60900/IEC 60900, fully insulated blade
- > Tip to DIN ISO 2380-1 form B
- > 3-component handles Power-Grip³ with hanging hole
- > Ergonomic handle design enables precise and fatigue-free working
- > Positive-fit joint of handle and blade for optimum transmission of force
- > Type of drive marked at end of the handle
- > Blade from GEDORE molybdenum-vanadium-Plus tempered steel



Code	No.	⊖ mm ↲	↳ mm ↲	⚖ kg
1612220	VDE 2170 2,5	2.5	160	0.038
1612247	VDE 2170 3,5	3.5	185	0.055
1612255	VDE 2170 4	4.0	185	0.058
1612271	VDE 2170 5,5	5.5	225	0.095
1612298	VDE 2170 6,5	6.5	260	0.134

VDE 2160-2170 SCREWDRIVER SET

6 pieces



Code	No.	Contents	⚖ kg
1616048	VDE 2170-2160 PH 06	⊖ VDE 2170 3.5 4 5.5 6.5 ⊕ VDE 2160 PH1 PH2	660