

4549

## TORQUE WRENCH TORCOFIX K

1-50Nm / 0.75-37lbf·ft

### Use:

- For use in almost all industrial manufacturing areas.
- For controlled nut and bolt tightening.

### Features:

- Adjustable torque wrench with a square drive and integrated ratchet head function.
- For controlled bi-directional tightening.
- Interchangeable mushroom head square drive with ball-locking mechanism as per DIN 3120.
- In accordance with DIN EN ISO 6789, traceable to national norms.
- Actuation accuracy: +/- 3% tolerance of the scale set to torque.
- Lever breaking mechanism with a castor guarantee tactile impulse and audible actuation signals.
- Double scale Nm and lbf.ft behind window with magnifying effect.
- Black plastic handgrip with slip-resistant ribbed surface.
- Full-metal construction from high strength aluminium alloy.
- Additional micrometer scale with a Nm graduation of 0.1, 0.25, 0.5 or 1Nm.
- Supplied with a calibration certificate.
- Unique serial number for traceability.

1/4"

3/8"



| Code    | No.     | □"  | ■    | Nm    | lbf-in   | □mm | kg    |
|---------|---------|-----|------|-------|----------|-----|-------|
| 2201429 | 4549-00 | 1/4 | 6.3  | 1-5   | 0.75-3.7 | 225 | 0.323 |
| 1545132 | 4549-02 | 1/4 | 6.3  | 2-25  | 1.5-18   | 285 | 0.450 |
| 1545140 | 4549-05 | 3/8 | 10.0 | 10-50 | 7.5-37   | 335 | 0.540 |

4550

## TORQUE WRENCH TORCOFIX K

40-750Nm / 30-550lbf·ft

### Use:

- For use in almost all industrial manufacturing areas.
- For controlled nut and bolt tightening.

### Features:

- Adjustable torque wrench with a square drive and integrated ratchet head function.
- For controlled bi-directional tightening.
- Interchangeable mushroom head square drive with ball-locking mechanism as per DIN 3120.
- In accordance with DIN EN ISO 6789, traceable to national norms.
- Actuation accuracy: +/- 3% tolerance of the scale set to torque.
- Lever breaking mechanism with a castor guarantee tactile impulse and audible actuation signals.
- Double scale Nm and lbf.ft behind window with magnifying effect.
- Black plastic handgrip with slip-resistant ribbed surface.
- Sturdy, varnished tubular steel construction, with zinc plated ratchet head and top grade plastic parts.
- Additional micrometer scale with a Nm graduation of 0.1, 0.25, 0.5 or 1Nm.
- Supplied with a calibration certificate.
- Unique serial number for traceability.

1/2"

3/4"



| Code    | No.     | □"  | ■    | Nm      | lbf-ft  | □mm  | kg   |
|---------|---------|-----|------|---------|---------|------|------|
| 7601610 | 4550-20 | 1/2 | 12.5 | 40-200  | 30-150  | 485  | 1.10 |
| 7674330 | 4550-40 | 3/4 | 20.0 | 80-400  | 60-300  | 665  | 1.86 |
| 7674760 | 4550-55 | 3/4 | 20.0 | 110-550 | 80-405  | 960  | 3.56 |
| 1521365 | 4550-75 | 3/4 | 20.0 | 150-750 | 110-550 | 1240 | 4.50 |

4101

## TORQUE WRENCH TORCOFIX SE

5-50Nm / 3.5-37lbf·ft

### Use:

- For use in almost all industrial manufacturing areas.
- For controlled nut and bolt tightening.

### Features:

- Adjustable torque wrench with a 9x12 rectangular cavity.
- For controlled bi-directional tightening.
- With pin-locking mechanism for replaceable 9x12 spanner end fittings.
- In accordance with DIN EN ISO 6789, traceable to national norms.
- Actuation accuracy: +/- 3% tolerance of the scale set to torque.
- Lever breaking mechanism with a castor guarantee tactile impulse and audible actuation signals.
- Double scale Nm and lbf.ft behind window with magnifying effect.
- Full-metal construction from high strength aluminium alloy.
- Supplied with a calibration certificate.
- Unique serial number for traceability.

9x12



| Code    | No.     | □mm" | Nm   | lbf-in | □mm | kg    |
|---------|---------|------|------|--------|-----|-------|
| 1646206 | 4101-05 | 9x12 | 5-50 | 3.5-37 | 325 | 0.640 |

4150-4151

## TORQUE WRENCH TORCOFIX FS

2-200Nm

### Use:

- For use in almost all industrial manufacturing areas.
- For controlled nut and bolt tightening.

### Features:

- Adjustable torque wrench with a 9x12 or 14x18 rectangular cavity.
- For controlled bi-directional tightening.
- With pin-locking mechanism for replaceable 9x12 or 14x18 spanner end fittings.
- In accordance with DIN EN ISO 6789, traceable to national norms.
- Actuation accuracy: +/- 3% tolerance of the scale set to torque.
- Lever breaking mechanism with a castor guarantee tactile impulse and audible actuation signals.
- Double scale Nm and lbf.ft behind window with magnifying effect.
- Full-metal construction from high strength aluminium alloy.
- Supplied with a calibration certificate.
- Unique serial number for traceability.

9x12

14x18



| Code    | No.     | □mm"  | Nm     | □mm | kg    |
|---------|---------|-------|--------|-----|-------|
| 7601960 | 4150-25 | 9x12  | 2-25   | 180 | 0.210 |
| 7602180 | 4150-50 | 9x12  | 5-50   | 240 | 0.270 |
| 7602850 | 4150-85 | 9x12  | 15-85  | 320 | 0.340 |
| 7603580 | 4151-20 | 14x18 | 20-200 | 400 | 0.750 |