8562

TORQUE WRENCH DREMOMETER

50-300Nm / 35-220lbf·ft

Use:
- For use in almost all industrial manufacturing areas.
- For controlled nut and bolt tightening.

Features:
- Adjustable torque wrench with a 1/2" single square drive for controlled clockwise tightening.
- 1/2" square drive with ball-locking mechanism as per DIN 3120.
- In accordance with DIN EN ISO 6789, traceable to national norms.
- Automatic short path actuation with tactile impulse and audible signal.
- Actuation accuracy: +/- 3% tolerance of the scale set to torque.
- Full-metal construction from high strength aluminium alloy.
- Double scale Nm and lbf.ft with scale graduation of 1Nm and 10lbf.in.
- Supplied with a calibration certificate.
- Unique serial number for traceability.

Code	Type	No.	■ "	■	Contents		Nm	lbf·ft	⊢ mm ⊣	kg
7685450		8562-01	1/2	12.5		in plastic box	5Nm / 5lbf·ft	50-300	35-220	617	2.0

8573

TORQUE WRENCH DREMOMETER

40-200Nm / 30-150lbf·ft

Use:
- For use in almost all industrial manufacturing areas.
- For controlled nut and bolt tightening.

Features:
- Adjustable torque wrench with a 1/2" single square drive for controlled clockwise tightening.
- 1/2" square drive with ball-locking mechanism as per DIN 3120.
- In accordance with DIN EN ISO 6789, traceable to national norms.
- Automatic short path actuation with tactile impulse and audible signal.
- Actuation accuracy: +/- 3% tolerance of the scale set to torque.
- Full-metal construction from high strength aluminium alloy.
- Double scale Nm and lbf.ft with scale graduation of 1Nm and 10lbf.in.
- Supplied with a calibration certificate.
- Unique serial number for traceability.

Code	Type	No.	■ "	■	Contents		Nm	lbf·ft	⊢ mm ⊣	kg
7685530		8573-00	1/2	12.5		in plastic box	5Nm / 5lbf·ft	40-200	30-150	551	1.40

8563 D & DR

TORQUE WRENCH DREMOMETER

140-760Nm / 105-560lbf·ft

Use:
- For use in almost all industrial manufacturing areas.
- For controlled nut and bolt tightening.

Features:
- Adjustable torque wrench with a 3/4" single square drive for controlled clockwise tightening.
- 3/4" square drive with ball-locking mechanism as per DIN 3120.
- In accordance with DIN EN ISO 6789, traceable to national norms.
- Automatic short path actuation with tactile impulse and audible signal.
- Actuation accuracy: +/- 3% tolerance of the scale set to torque.
- Full-metal construction from high strength aluminium alloy.
- Double scale Nm and lbf.ft with scale graduation of 1Nm and 10lbf.in.
- Supplied with a calibration certificate.
- Unique serial number for traceability.

Code	Type	No.	■ "	■	Contents		Nm	lbf·ft	⊢ mm ⊣	kg
7670180		8563-01 with extension tube	3/4	20		in plastic box	5Nm / 5lbf·ft	140-760	105-560	1400	5.00
7691500		8563-10	3/4	20		in plastic box		140-760	105-560	812	2.90