

SOLUTIONS KITS

FEATURES

- All the tools needed to **ensure a perfect joint**, every time.
- Works for plastic pipe such as PVC, CPVC, PP, ABS and PE.
- Cutter provides quick, square and clean cut on plastic pipe.

These kits contain tools required to install a perfect joint every time to prevent failures between pipe and fitting. Quick Release™ Cutter produces a square, clean cut which is imperative for proper, even stab depth into fittings and for reducing leak potential. DEB4 and DEB1 deburring tools produce even, consistent chamfer ensuring proper fitting penetration depth. And, at the same time, allow the solvent cement to move to the correct part of the pipe (side) for greater surface area solvent weld. The IC1SL Internal Pipe Cutter (in some kits) yields a uniform internal cut in hard-to-reach places where a tubing cutter will not fit. All tools are contained in a durable, hard plastic case.

	Catalog	Item	Description	Weight	
	No.	Code	Description		kg
	TC2PPDEB1-2SK	04142	TC2QPVC, DEB1IPS & DEB1-2IPS with case	5.6	2.5
	TC3PPSK	04151 TC3QPVC, DEB4 & DEB1IPS with case		6.9	3.1
	TC3-636SK	04155	TC3QPVC, DEB4 & IC1SL with case	6.9	3.1
	TC4-636SK	04156	TC4QPVC, DEB4 & IC1SL with case	7.1	3.2
	TC2PPSK	04157	TC2QPVC, DEB4 & DEB1IPS with case		2.5
F	TC-AQRSK	04162	TC2QPVC, TC4QPVC, DEB4 & DEB1IPS with case	8.45	3.8
	ALC: ALC: ALC: ALC: ALC: ALC: ALC: ALC:				





FEATURES

- One tool does a range of pipe.
- Takes 2 minutes to attach to pipe and peel 6" PE.
- Creates a **uniformly** peeled surface.
- Works well even on out-of-round pipe.

PE Pipe Peeler prepares the outside diameter of polyethylene pipe for electrofusion by removing the oxidized layer and contaminates. PE Pipe Peeler can be used on the edge of the pipe or anywhere along the pipe with sufficient clearance for turning the tool around the pipe. Chain with thermoplastic rollers of acetel copolymer and plated side plates resist corrosion. Spring-loaded blade keeps consistent pressure on the pipe for a smooth finished surface. This blade tension means the blade does not skip. Its carbide blade provides a cutting edge on each side. Rotate blade before replacement and receive three additional cutting edges.

Catalog No.	Itam	Pipe Capacity		Weight	
	Item Code	in-nom.	actual 0.D. mm	lbs	kg
PEPEEL6	04631	1 ¹ / ₂ - 6*	48 - 168	3.1	1.4
PEPEEL12	04632	6-12	168 - 324	10.9	5.0

^{*}O D must be 1.9" or more



FEATURES

• Flare water service lines easily with this innovative and inexpensive tool.

Flare Tools for PE Water Service Lines form a permanent cold flare with ten easy revolutions to connect PE 160 psi water service tubing (SDR 9), using inexpensive, standard AWWA flare fittings for CTS tubing. These tools flare medium and high density PE.

Catalog	Item	CTS Tubing	Weight	
No.	Code	in-nom.	lbs	kg
SFPE3/4*	04200	3/4"	1.9	0.9
SFPE1*	04202	1"	2.2	1.0

*EXCLUSIVE



