

LXP-2

LXP-10B

LXP-10A

LIGHT METERS



The new LXP digital light meter family allows for a very precise measurement of illuminance. Thanks to very high resolution LXP-10B (resolution 0.01 lx) and LXP-10A (resolution 0.001 lx) allows for escape route emergency light measurement. All of three light meter have built-in memory for measurement result storing, and additional function making work much easier.

The most important features of new LXP family are:

- Measurement resolution **LXP-2** – 0.1 lx (0.01 fc), **LXP-10B** – 0.01 lx (0.001 fc), **LXP-10A** - 0.001 lx (0.001 fc).
- High accuracy and fast response.
- Data-hold function for holding measuring values.
- Automatic zeroing,
- No need for correction factors calculating for different light sources thanks to a very good fit spectral sensitivity guaranteeing the correct measurement of intensity of the illumination regardless of the nature of radiation,
- Peak-hold function for tracing the peak signal of light pulse with duration longer than 0.1 s (0.4 s for LXP-2) and less than 1 s,
- Capable of selecting measuring mode in Lux or FC scale alternatively.
- Auto power off (5,10 or 15minutes) or disable AUTO power off.
- Maximum and minimum measurements.
- Relative reading.
- Easy to read large backlit display
- USB output connect with PC.
- Data transmission via radio connection using an optional adapter OR-1 (only LXP-10B, LXP-10A)
- four - LXP-2, five - LXP-10B and six measurement ranges - LXP-10A .
- Built-in memory - 99 result for LXP-2 or 999 for LXP-10A and LXP-10B, with can be checked in the meter or PC.
- 16000 values records data logger (traceable only in PC)

Sonel S.A.
Wokulskiego 11
58-100 Świdnica, PL
tel. +48 74 85 83 860
fax +48 74 85 83 809

export@sonel.pl
www.sonel.pl

LXP-2 / 10B / 10A

Illuminance measurement probe LP-1

Display Range [lx]	Resolution [lx]	Spectral uncertainty	Accuracy
0...399,9	0,1	$f_1 \leq 6\%$	$\pm(5\% + 5 \text{ cyfr})$
400...3999	1		
4,00 k...19,99 k	0,01 k		

Display Range [fc]	Resolution [fc]	Spectral uncertainty	Accuracy
0...39,99	0,01	$f_1 \leq 6\%$	$\pm(5\% + 5 \text{ cyfr})$
40,0...399,9	0,1		
400...1999	1		

- display result in lx or fc
- meter class B

Illuminance measurement probe LP-10B

Display Range [lx]	Resolution [lx]	Spectral uncertainty	Accuracy
0...39,99	0,01	$f_1 \leq 6\%$	$\pm(5\% + 5 \text{ digits})$
40,0...399,9	0,1		
400...3999	1		
4,00 k...39,99 k	0,01 k		
40,0 k...399,9 k	0,1 k		

Display Range [fc]	Resolution [fc]	Spectral uncertainty	Accuracy
0...3,999	0,001	$f_1 \leq 6\%$	$\pm(5\% + 5 \text{ digits})$
4,00...39,99	0,01		
40,0...399,9	0,1		
400...3999	1		
4,00 k...39,99 k	0,01 k		

- display result in lx or fc
- meter class B

Illuminance measurement probe LP-10A

Display Range [lx]	Resolution [lx]	Spectral uncertainty	Accuracy
0...3,999	0,001	$f_1 \leq 2\%$	$\pm(2\% + 5 \text{ digits})$
4,00...39,99	0,01		
40,0...399,9	0,1		
400...3999	1		
4,00 k...39,99 k	0,01 k		

Display Range [fc]	Resolution [fc]	Spectral uncertainty	Accuracy
0...3,999	0,001	$f_1 \leq 2\%$	$\pm(2\% + 5 \text{ digits})$
4,00...39,99	0,01		
40,0...399,9	0,1		
400...3999	1		
4,00 k...39,99 k	0,01 k		

- display result in lx or fc (display result in fc with reduced resolution due to limitations of display)

- meter class A

LXP-2



LXP-10



LP-1



LP-10A



LP-10B



Standard accessories:

- LXP-2 or LXP-10 meter,
- 9 V battery,
- measurement probe LP-1, LP-10B or LP-10A,

Warning: LP-1 probe is not compatible with LXP-10A and LXP-10B meter

- USB cable,
- data CD with "SONEL Reader" software,
- operating manual,
- carrying case,
- warranty card.

Additional accessories:

- USB interface for radio transmission OR-1 (LXP-10A/B only) **WADAUSBOR1**

Rated operational conditions:

- operating temperature and humidity $0\dots50^\circ\text{C}$
 0% to 80% RH
 $-20\dots70^\circ\text{C}$
 0% to 70% RH
- storage temperature and humidity

Other technical data:

- display $3\frac{1}{2}$ digit LCD with high speed 40 segment bargraph
„OL“ displayed
- over range indication
- spectral response CIE photopic (CIE human eye response curve)
 $\pm 3\%$
- cosine response (f_2') $1,3$ times/sec
- sampling rate
- power supply battery 9V or rechargeable battery 8,4 V
- photo detector one silicon photo diode and spectral response filter
- memory 99 results LXP-2, 999 results LXP-10
approx. 150cm
- photo detector lead length $115 \times 60 \times 20\text{mm}$
- photo detector dimensions $170 \times 80 \times 40\text{mm}$
- meter dimensions 390g
- weight
- data transmission USB cable or wireless radio interface OR-1 (LXP-10B, LXP-10A only)